Product Sheet

bain de ville 6030



Product No.

Model Alcove, Left	TMU BBVBRAOLT-XX	Soaker BBVBRAOLN-XX
Model Alcove, Right	TMU BBVBRAORT-XX	Soaker BBVBRAORN-XX

ThermoMasseur (TMU)

Air Jet System	\$3,595	
Jets	42	
1 heated backrest	Included	
Mia® Control	Included	
BU-Touch Control Application BUTOUCH	\$495	
Geysair®	Included	
AromaCloud® BAROMAC	\$590	
Illuzio Chromatherapy BCHRO6	\$995	

Soaker	\$1,930
AromaCloud® BAROMAC	\$590
Illuzio Chromatherapy BCHRO6	\$995
WarmTouchShell® BWTS	\$1,125
DOT Control	Included with therapy

UltraVelour Matte Finish (white only) BVEL1		\$650	
Control (TMU only) p.13			
MiaPlus®# BMIAP1-XX		\$285	
Universal Armrests BGBGU-XX p.16			
White 01		\$895	
Bath Pillow BPILLOW p.252		\$240	
Comfort Cushion BCUSHIONA p.253		\$540	
Grey 05 🜑 Black 06			
Drain & Overflow p.14	Integrated ZenFlow ⁺ BOVERINZF-XX	Integrated with trim BOVERIN-XX	16" x 35"*** BOVER16-XX
Chrome 07	\$40	\$70	\$95
White 01 Biscuit 02	Incl.	\$40	\$125
Brushed Nickel 09	\$40	\$70	\$235
Polished Nickel 10	\$40	\$70	\$235
Oil-rubbed Bronze 11	N/A	N/A	\$235
Matte Black 19 Satin Brass 18	\$95	\$125	N/A
Matte White 32	\$40	\$70	N/A
If Required by Construction Code			
Brass drain & overflow kit [‡] BDRCOB		\$240	
Brass drain kit‡ BDRCB		\$60	
16" x 35" Cable driven brass drain & overflow kit BOVERBR		\$240	

Features

Installation Type	Alcove (3 walls)
Integrated Skirt & Tile Flange (specify right or left)	Installed & Included
No. of bathers 🕴 Imp. gallons 33 US gallons 39	
Integrated Drain & Overflow – ZenFlow [†] BOVERINIZF-XX	
White 01 Biscuit 02	Installed & Included
Standard Bath Color p.17	
White 01 Biscuit 02	Included

With the AromaCloud® and/ ÷ or Control on the deck, a complete shower door cannot be installed.

Options UPCHARGE APPLICABLE

Finish p.17

Don't forget to specify the finish of the Integrated drain & overflow.

#

- ZenFlow: Integrated overflow without a trim. The MiaPlus® Control is included when purchasing Chromatherapy on a TMU. When ordered with Integrated drain & overflow.
- ŧ



Product Sheet

bain de ville 6030



Technical Specifications



Letter	Description	Measure
A	Total length	60"
В	Bathing well length	46 %"
С	Total width	30"
D	Bathing well width	20 1/2"
E	Outer edge to center drain (right side)	14 1⁄8"
F	Deck width (drain side)	3 3⁄16"
G	Deck width (backrest)	4 3/8"
н	Deck width (wall side)	2"
I	Deck width (skirt side)	3 1/8"
J	Outer edge to center drain Integrated drain & overflow (front)	10 3⁄8"
К	Outer edge to center of overflow Drain & overflow 16" x 35" only	2 3⁄8"
L	Tile flange height	1"
М	Height from floor to bottom of deck	17"
N	Slope of backrest	21°
0	Maximum water level	12 1/4"

Turbine position (TMU)
Indicates WarmTouchShell® position (Soaker)

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.	Approx. shipping weight	125 lb
Turbine	Turbine is factory installed, so access to the pump must be at least 18" x 22". Standard	Turbine power	550 W
connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.		Air heater	600 W
Others	The Geysair® is located on the same side as the heated backrest. It must not be relocated. It must be connected to the hot water supply and be accessible (provide access).		
	Integrated tile flange is included (specify right or left).	Warranty	

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

•	
Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

* Some restrictions apply | www.bainultra.com/warranty

Dimensions are subject to change; measured at external edges. Bathing well measured at air jet level. Tolerance: ± 0.25 " (± 0.64 cm). Ensure bathtub is received prior to any construction. BainUltra® is not responsible for any preparatory work done before product arrival.