Freestanding 66" x 36" x 27"

cella 6636



Product No.

Model Flat deck	TMU BBCLOFNOT-XX	Soaker BBCLOFNON-XX
Model Rolled deck	TMU BBCLOFPOT-XX	Soaker BBCLOFPON-XX

ThermoMasseur (TMU)

Air Jet System	\$10,145
Jets	38
1 heated backrest	Included
MiaPlus® Control*	Included
BU-Touch Control Application BUTOUCH	Included
Geysair®	Included
AromaCloud®** BAROMAC	\$590
Illuzio Chromatherapy BCHRO6	\$995
2nd heated backrest (WTS-1 zone) BSHB	\$1,125

Soaker	\$7,260
AromaCloud®** BAROMAC	\$590
Illuzio Chromatherapy BCHRO6	\$995
WarmTouchShell® BWTS	\$1,125
DOT Control	Included with therapy
2nd WarmTouchShell® BWTS2	\$370

Features

Installation Type		Freestanding
No. of bathers 👬 Imp. gal	lons 40 US gallons 48	
Standard Bath Color p.17		
○ White 01 ○ Biscuit 0	2	Included
Claw Feet (specify finish)	BFEET-XX p.16	
Chrome 07 Brushed Nickel 09 Polished Nickel 10	Oil-rubbed Bronze 11 Unplated 00	Included

1800 463-2187

Options UPCHARGE APPLICABLE

Universal Armrests BGBGU-XX p.16	
White 01	\$895
For Air Supply Only	
Decorative pipe (1 ½" x 6")	\$55
Decorative pipe (1 ½" x 24")	\$200
Pipe concealer (3" x 5 1/4")	\$105
Elbow (45°)	\$80
Elbow (90°)	\$105
Bath Pillow BPILLOW p.252	\$240
Comfort Cushion (with flat deck only) BCUSHIONA p.253	\$540
Grey 05 Black 06	
Drain & Overflow p.14	D13 BOVERD13-XX
Chrome 07	\$500
Brushed Nickel 09	\$500
Polished Nickel 10	\$500
Unplated 00	\$500
Oil-rubbed Bronze 11	\$500

Don't forget to indicate raised or flat deck.

Specify the finish for the drain & overflow.

- For TMU, control must be wall-mounted. Faucets must be freestanding or wall-mounted.
 The AromaCloud® is built into the deck (factory installed).

For the installer Scan to view installation video (3:20 min) →




cella 6636







Technical Specifications



Letter	Description	Measure
A	Outside edge to center drain	11 ½"
В	Outside edge to overflow	4 5/8"
С	Total length	66"
D	Total width	36"
E	Bathing well length	42 3/8"
F	Bathing well width	22 1/4"
G	Deck width	4 1/4"
Н	Flat surface width	3"
I	Rolled deck width	4 3/4"
J	Height from bottom of lip to top deck	2 1/2"
K	Height from clawfoot to top of lip	27 3/4"
L	Height from clawfoot to top of lip	26 3/4"
М	Height from bottom of drain to center of overflow	16 %"
N	Maximum water level	14 1/8"
0	Slope of backrests	25°
Р	Length between clawfeet	34 %"
Q	Width between clawfeet	23 ½"
R	Center drain to center air intake	3 1/4"

Hot water supply required

The hot water supply should be 70% or more of the bath's total water capacity.

Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.

Others

The Geysair® is located on the same side as the heated backrest. It must not be relocated. It must be connected to the hot water supply and be accessible (provide access).

There is a height difference for the rolled deck (see drawing Detail A). Faucets must be freestanding or wall-mounted. The turbine must be remotely installed. TMU: Control must be wall-mounted. Soaker: DOT Controls are located on either sides of the AromaCloud® (see page 9, position of DOT Control).

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

Cutting template	# 90000055
Approx. shipping weight	285 lb
Turbine power	550 W
Air heater	600 W

Warranty

Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

^{*} Some restrictions apply | www.bainultra.com/warranty