Product Sheet

naos 7240

Freestanding $72" \times 40" \times 25"$



Product No.

Model Flat deck	TMU BBNUOFNOT-XX	Soaker BBNUOFNON-XX
Model Rolled deck	TMU BBNUOFPOT-XX	Soaker BBNUOFPON-XX

ThermoMasseur (TMU)

Air Jet System	\$12,055
Jets	40
1 heated backrest	Included
MiaPlus® Control*	Included
BU-Touch Control Application BUTOUCH	Included
Geysair®	Included
AromaCloud®** BAROMAC	\$590
Illuzio Chromatherapy BCHRO6	\$995
2nd heated backrest (WTS-1 zone) BSHB	\$1,125

Soaker	\$9,040	
AromaCloud®** BAROMAC	\$590	
Illuzio Chromatherapy BCHRO6	\$995	
WarmTouchShell® BWTS	\$1,125	
DOT Control	Included with therapy	
2nd WarmTouchShell® BWTS2	\$370	

Features

Installation Type	Freestanding	
No. of bathers 🐳 Imp. gallons 49 US gallons 59)	
Standard Bath Color p.17		
White 01 Biscuit 02	Included	

Options UPCHARGE APPLICABLE

\$895
\$55
\$200
\$105
\$80
\$105
\$240
\$540
D13 BOVERD13-XX
\$500
\$500
\$500
\$500
\$500

Don't forget to indicate flat or rolled deck.

For TMU, control must be wall-mounted. Faucets must be freestanding or wall-mounted.
** The AromaCloud® is built into the deck (factory installed).



https://bainultra.com/sites/default/files/ product_files/product-sheet-balneo-naos-7240.pdf

For the installer



naos 7240





Technical Specifications

Rolled deck



Letter	Description	Measure
A	Outside edge to center drain	11 3⁄4"
В	Outside edge to overflow	4 3⁄8"
С	Total length	72"
D	Total width	40"
E	Bathing well length	46 1/8"
F	Bathing well width	24 1/8"
G	Deck width	4 5/8"
н	Flat surface width	3 %"
I	Rolled deck width	5 5⁄8"
J	Height from bottom of lip to top deck	21/2"
к	Height from bottom of bath to top deck	26 3⁄4"
L	Height from bottom of bath to top deck	25 ¾"
М	Height from bottom of drain to center of overflow	16 5/8"
N	Maximum water level	14 7⁄8"
0	Slope of backrests	27°
P	Base length	64 ¼"
Q	Base width	35 %"
R	Center drain to center air intake	5"

▲ AromaCloud® position ● Indicates heated backrest (TMU)
(i) Indicates WarmTouchShell® position (Soaker)

The hot water supply should be 70% or more of the bath's total water capacity.	Cutting template	# 90000001
Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz,	Approx. shipping weight	285 lb
dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.	Turbine power	550 W
	Air heater	600 W
The Geysair® is located on the same side as the heated backrest. It must not be relocated. It must be connected to the hot water supply and be accessible (provide access).		
There is a height difference for the rolled deck (see drawing Detail A). Faucets must be freestanding or wall-mounted. The turbine must be remotely installed. TMU: Control must be wall-mounted. Soaker: DOT Controls are located on either sides of the AromaCloud® (see page 9, position of DOT Control).	Warranty	
	Controls-LED-Geysair*	5 years
	Bath & turbine*	20 years
	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum. The Geysair® is located on the same side as the heated backrest. It must not be relocated. It must be connected to the hot water supply and be accessible (provide access). There is a height difference for the rolled deck (see drawing Detail A). Faucets must be freestanding or wall-mounted. The turbine must be remotely installed. TMU: Control must be wall-mounted. Soaker: DOT Controls are located on either sides of the	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum. Approx. shipping weight Turbine power The Geysair® is located on the same side as the heated backrest. It must not be relocated. It must be connected to the hot water supply and be accessible (provide access). Aurice access and the same side as the heated backrest. It must not be relocated. It must be connected to the hot water supply and be accessible (provide access). There is a height difference for the rolled deck (see drawing Detail A). Faucets must be freestanding or wall-mounted. The turbine must be remotely installed. TMU: Control Same located on either sides of the Warranty

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

* Some restrictions apply | www.bainultra.com/warranty

Dimensions are subject to change; measured at external edges. Bathing well measured at air jet level. Tolerance: ± 0.25 " (± 0.64 cm). Ensure bathtub is received prior to any construction. BainUltra® is not responsible for any preparatory work done before product arrival.