esthesia 6638



Soaker BEAMRDOON-XX

Soaker BEAMRD10N-XX

Product No.

Model Standard 2" deck	TMU BEAMRDOOT-XX
Model Slim deck 1/2"	TMU BEAMRD10T-XX

ThermoMasseur (TMU)

Air Jet System	\$5,875
Jets	38
1 heated backrest	Included
MiaPlus® Control	Included
BU-Touch Control Application BUTOUCH	\$495
Geysair®	Included
AromaCloud® BAROMAC	\$590
Illuzio Chromatherapy BCHRO6	\$995
2nd heated backrest (WTS-1 zone) BSHB	\$1,125

Soaker	\$2,975
AromaCloud® BAROMAC	\$590
Illuzio Chromatherapy BCHRO6	\$995
WarmTouchShell® BWTS	\$1,125
DOT Control	Included with therapy
2nd WarmTouchShell® BWTS2	\$370

Options UPCHARGE APPLICABLE Finish p.17

Finish p.17		
UltraVelour Matte Finish (white only) BVEL1	\$650	
Universal Armrests BGBGU-XX p.16		
White 01	\$895	
Bath Pillow BPILLOW p.252	\$240	
Comfort Cushion BCUSHIONA p.253	\$540	
Grey 05 🜑 Black 06		
Drain & Overflow p.14	Integrated ZenFlow† <i>BOVERINZF-XX</i>	Integrated with trim BOVERIN-XX
White 01 Biscuit 02	Incl.	\$40
Chrome 07	\$40	\$70
Brushed Nickel 09	\$40	\$70
Polished Nickel 10	\$40	\$70
Matte Black 19 Satin Brass 18	\$95	\$125
If Required by Construction Code		
Brass drain & overflow kit BDRCOB	\$240	
Brass drain kit BDRCB	\$60	

Features

loataroo	
Installation Type	Drop-in
No. of bathers 👬 Imp. gallons 49 US gallons 59	
Integrated Drain & Overflow – ZenFlow [†] BOVERINIZF-01	
O White 01	Installed & Included
Standard Bath Color p.17	
White 01 Biscuit 02	Included

Don't forget to specify the finish of the Integrated drain & overflow.

Don't forget to specify the deck height (1/2" or 2").

 $^{\scriptscriptstyle \dagger}$ $\,$ ZenFlow: Integrated overflow without a trim.



esthesia 6638

66" x 38" x 21"





Technical Specifications



Letter	Description	Measure
A	Total length	66"
В	Total width	38"
С	Bathing well length	47 3⁄8"
D	Bathing well width	23"
E	Deck width (narrowest point)	2 5⁄8"
F	Deck width at 2nd backrest	2 5⁄8"
G	Deck to drain center	19"
н	Total height	21''
I	Height from bottom of bath to bottom of standard deck 2"	19"
J	Slope of 2nd backrest	21°
К	Slope of backrest	26°
L	Deck to edge of overflow	3 1⁄2"
М	Height from bottom of drain to center of overflow	16 5⁄8"
N	Maximum water level	15 1/8"
0	Height from bottom to top of deck	2"
P	Height from bottom to top of slim deck	1/2"

● Turbine position (TMU) ● Indicates heated backrest (TMU) ③ Indicates WarmTouchShell® position (Soaker)

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2° x 4" minimum.
Others	The Geysair® is located on the same side as the heated backrest. It must not be relocated It must be connected to the hot water supply and be accessible (provide access).

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

Cutting template	# 90000066
Approx. shipping weight	120 lb
Turbine power	550 W
Airheater	600 W

Warrantv

manany		
Controls-LED-Geysair*	5 years	
Bath & turbine*	20 years	

* Some restrictions apply | www.bainultra.com/warranty

Dimensions are subject to change; measured at external edges. Bathing well measured at air jet level. Tolerance: $\pm 0.25^{"}$ (± 0.64 cm). Ensure bathtub is received prior to any construction. BainUltra® is not responsible for any preparatory work done before product arrival.