## Freestanding 66" x 36" x 28"

# evanescence oval 6636



### Product No.

Model Freestanding TMU BEVLOFOOT-XX Soaker BEVLOFOON-XX

## ThermoMasseur (TMU)

Air Jet System	\$10,420
Jets	35
1 heated backrest & headrest	Included
MiaPlus® Control*	Included
BU-Touch Control Application BUTOUCH	Included
Geysair®	Included
AromaFlow BAROMAF	\$950
Illuzio Chromatherapy BCHRO6	\$995
2nd heated backrest (WTS-1 zone) BSHB	\$1,125

Soaker	\$7,800
AromaFlow BAROMAF	\$950
Illuzio Chromatherapy BCHRO6	\$995
WarmTouchShell® BWTS	\$1,125
DOT Control	Included with therapy
2nd WarmTouchShell® BWTS2	\$370

## **Features**

Installation Type			Freestanding
No. of bathers 👬	Imp. gallons 42	US gallons 51	Raised headrests 2
Integrated Drain 8	k Overflow — Zen	Flow† BOVERIA	IIZF-01
◯ White 01			Installed & Included
Standard Bath Co	lor p.17		
◯ White 01			Included

#### **Options** UPCHARGE APPLICABLE

•		
Bath Color p.17		
Black / White 66	\$475	
Finish p.17		
UltraVelour Matte Finish (white only) BVEL2	\$850	
Universal Armrests BGBGU-XX p.16		
White 01	\$895	
Bath Pillow BPILLOW p.252	\$240	
Drain & Overflow p.14	Integrated ZenFlow <sup>†</sup> BOVERINZF-XX	Integrated with trim BOVERIN-XX
White 01	Incl.	\$40
Matte White 32 Chrome 07 Brushed Nickel 09 Polished Nickel 10	\$40	\$70
Matte Black 19 Satin Brass 18	\$95	\$125
Island Tub Drain™*** p.15		
Island Tub Drain™ BISLDD	\$260	
Cast Iron Island Tub Drain™ BISLDDCI	\$310	
If Required by Construction Code or installed with ITD		
Brass drain & overflow kit BDRCOB	\$240	
Brass drain kit BDRCB	\$60	

- Don't forget to specify the finish of the Integrated drain & overflow.
- <sup>†</sup> ZenFlow: Integrated overflow without a trim.
   <sup>\*</sup> For TMU, control must be wall-mounted. Faucets must be freestanding or wall-mounted.
   \*\*\* An Island Tub Drain™ is required when there is no access under the bath.






# evanescence oval 6636







### **Technical Specifications**



AromaFlow is installed.

Letter	Description	Measure
A	Total length	66"
В	Total width	36"
С	Bathing well length	41 3/4"
D	Bathing well width	23 %"
E	Deck width	11/4"
F	Center drain to center air intake	3 1/8"
G	Total height to headrest	28"
Н	Minimum height to center	25"
I	Maximum water level Maximum water level with AromaFlow	15 7/8" 15 5/16"
J	Base length	50"
K	Base width	26 1/4"
L	Slope of backrests	31°
М	Center drain to center air intake	4 1/4"
<ul><li>Indica</li></ul>	tes heated backrest (TMU) 🏿 Indicates Warn	nTouchShell® position (Soaker)

Hot water supply required

The hot water supply should be 70% or more of the bath's total water capacity.

Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary:

Others The Geysair® is

The Geysair® is located on the same side as the heated backrest. It must not be relocated. It must be connected to the hot water supply and be accessible (provide access).

Faucet must be freestanding or wall-mounted. The turbine must be remotely installed. Controls cannot be installed on the deck of the bath. The water level will vary when an

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

Cutting template	# 90000064
Approx. shipping weight	230 lb
Turbine power	550 W
Air heater	600 W

#### Warranty

•	
Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

<sup>\*</sup> Some restrictions apply | www.bainultra.com/warranty