## **Product Sheet**

# libra aurora 6634



## **Product No.**

Model Freestanding

TMU BLAKOFOOT-XX

Soaker BLAKOFOON-XX

## ThermoMasseur (TMU)

Air Jet System	\$9,330
Jets	40
1 heated backrest	Included
MiaPlus® Control <sup>†††</sup>	Included
BU-Touch Control Application BUTOUCH	Included
Geysair®	Included
AromaFlow <sup>tt</sup> BAROMAF	\$950
Illuzio Chromatherapy BCHRO6	\$995
2nd heated backrest (WTS-1 zone) BSHB	\$1,125

Soaker	\$6,980
AromaFlow <sup>††</sup> BAROMAF	\$950
Illuzio Chromatherapy BCHRO6	\$995
WarmTouchShell® BWTS	\$1,125
DOT Control	Included with therapy
2nd WarmTouchShell® BWTS2	\$370

#### **Options** UPCHARGE APPLICABLE

optiono of on Alide Ali LioAbee		
Bath Color p.17		
Black / White 66	\$475	
Finish p.17		
UltraVelour Matte Finish (white only) BVEL2	\$850	
Universal Armrests BGBGU-XX p.16		
White 01	\$895	
Bath Pillow BPILLOW p.252	\$240	
Drain & Overflow p.14	Integrated ZenFlow <sup>↑</sup> <i>BOVERINZF-XX</i>	Integrated with trim BOVERIN-XX
O White 01	Incl.	\$40
Matte White 32 Chrome 07	\$40	\$70
Matte Black 19 Satin Brass 18	\$95	\$125
Island Tub Drain™*** p.15		
Island Tub Drain™ BISLDD	\$260	
Cast Iron Island Tub Drain™ BISLDDCI	\$310	
If Required by Construction Code		
Brass drain & overflow kit BDRCOB	\$240	
Brass drain kit BDRCB	\$60	

## **Features**

Installation Type	Freestanding
No. of bathers 🐳 Imp. gallons 48 US gallons 58	
Integrated Drain & Overflow — ZenFlow <sup>†</sup> BOVERINIZE	-01
White 01	Installed & Included
Standard Bath Color p.17	
White 01	Included

Don't forget to specify the finish of the Integrated drain & overflow.

<sup>†</sup> ZenFlow: Integrated overflow without a trim.
<sup>††</sup> Control must be wall-mounted. Faucets must be freestanding or wall-mounted.
<sup>\*\*\*</sup> An Island Tub Drain™ is recommended when there is no access under the bath.
<sup>††</sup> When ordering an AromaFlow, an Integrated drain & overflow is mandatory (Included). Specify the finish of the drain.

https://bainultra.com/sites/default/ files/product\_files/product-sheet-libra-aurora-6634.pdf

#### For the installer

Scan to view installation video (3:20 min) →



## **Product Sheet**


## libra aurora 6634







### **Technical Specifications**



Letter	Description	Measure	
A	Total length	66"	
В	Total width	34"	
С	Bathing well length	44 1/16"	
D	Bathing well width	21"	
E	Deckwidth	1 7⁄16''	
F	Center drain to air intake (side)	4 1/2"	
G	Maximum total height	24"	
н	Height of deck upper lip	3"	
I	Base length	55"	
J	Slope of backrests	30°	
К	Maximum water level Maximum water level with AromaFlow	17 5/16'' 15 <sup>15</sup> /16''	
L	Base width	27"	
M	Height from drain to floor	3 1/2"	

Indicates heated backrest (TMU) (Indicates WarmTouchShell<sup>®</sup> position (Soaker)

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.
Turbine	Turbine is remotely installed; access to to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.
Others	The Geysair® is located on the same side as the heated backrest. It must not be relocated It must be connected to the hot water supply and be accessible (provide access).
	Faucet must be freestanding or wall-mounted. The turbine must be remotely installed. Controls cannot be installed on the deck of the bath. The water level will be lower when an AromaFlow is installed.

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

Cutting template	# 9000087
Approx. shipping weight	230 lb
Turbine power	550 W
Air heater	600 W

## Warranty

•	
Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

\* Some restrictions apply | www.bainultra.com/warranty

Dimensions are subject to change; measured at external edges. Bathing well measured at air jet level. Tolerance:  $\pm 0.25$ " ( $\pm 0.64$  cm). Ensure bathtub is received prior to any construction. BainUltra® is not responsible for any preparatory work done before product arrival.