meridian 6030



Product No.

Model Alcove, Right	TMU BMEBRIORT-XX	Soaker BMEBRIORN-XX
Model Alcove, Left	TMU BMEBRIOLT-XX	Soaker BMEBRIOLN-XX
Model Drop-in	TMU BMEBRIOOT-XX	Soaker BMEBRIOON-XX

ThermoMasseur (TMU)

Air Jet System	\$4,265	
Jets	37	
1 heated backrest	Included	
MiaPlus® Control	Included	
BU-Touch Control Application BUTOUCH	\$495	
Geysair®	Included	
AromaCloud®** BAROMAC	\$590	
Illuzio Chromatherapy BCHR06	\$950	
2nd heated backrest (WTS-1 zone) BSHB	\$995	

CHRO6	\$950	
FS-1zone) BSHB	\$995	

Soaker	\$1,875	
AromaCloud®** BAROMAC	\$590	
Illuzio Chromatherapy BCHRO6	\$995	
WarmTouchShell® BWTS	\$1,125	
DOT Control	Included with therapy	

Features

Installation Type	Drop-in & Alcove (3 walls)	
No. of bathers 🕴 Imp. gallons 41 US gallons 50		
Integrated Tile Flange (specify right or left)	Included	
Standard Bath Color p.17		
White 01 Biscuit 02	Included	

Options UPCHARGE APPLICABLE

Skirt p.254	Multifit BSMUL-XX	SJ-1 BSJ1-XX
White 01 Biscuit 02	\$695	\$715
Bath Pillow BPILLOW p.252	\$240	
Comfort Cushion BCUSHIONA p.253	\$540	
Grey 05 🗩 Black 02		
Drain & Overflow p.14	Integrated ZenFlow† <i>BOVERINZF-XX</i>	16" x 35" BOVER16-XX
Chrome 07	\$205	\$260
White 01 Biscuit 02	\$165	\$290
Brushed Nickel 09	\$205	\$290
Polished Nickel 10	\$205	\$290
Oil-rubbed Bronze 11	N/A	\$400
Matte Black 19 Satin Brass 18	\$260	N/A

16" x 35" Cable driven brass drain & overflow kit BOVERBR \$240

t

ZenFlow: Integrated overflow without a trim. The AromaCloud $^{\circledast}$ is built into the deck (factory installed). **



Product Sheet

meridian 6030





AromaCloud®

Technical Specifications



Letter	Description	Measure
A	Outside edge to center drain	11"
В	Outside edge to overflow	4"
С	Total length	60"
D	Total width	30"
E	Bathing well length	43 5⁄8"
F	Bathing well width	19 5⁄8"
G	Deck width	3 1⁄4"
н	Deck width at drain end	3 1/2"
I	Height from bottom of bath to top deck	20 1/2"
J	Height from bottom of bath to bottom of deck	19"
к	Height from bottom of bath to top of tile flange	21 1/2"
L	Tile flange height	1"
М	Height from bottom of drain to center of overflow	15 ¹³ ⁄16"
N	Maximum water level (Drain & overflow 16" x 35")	14 1⁄16"
0	Slope of backrest	24°
Arom	Claud@ pasition When the tile flange is added the	AreneeClevel®

AromaCloud® position. When the tile flange is added, the AromaCloud®

Indicates heated backrest (TMU) (1) Indicates WarmTouchShell® position (Soaker)

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.	Cutting template
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz,	Approx. shipping we
	dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary:	Turbine power
	2" x 4" minimum.	Air heater
Others	The Geysair® is located on the same side as the heated backrest. It must not be relocated. It must be connected to the hot water supply and be accessible (provide access).	
	There is a height difference for the integrated tile flange (see Detail A). Available with	Warranty
	or without integrated Tile Flange (specify right or left) at the same price.	Controls-LED-Gey

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

90000053 100 lb veight 550 W 600 W

Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

* Some restrictions apply | www.bainultra.com/warranty

Dimensions are subject to change; measured at external edges. Bathing well measured at air jet level. Tolerance: ±0.25" (±0.64 cm). Ensure bathtub is received prior to any construction. BainUltra® is not responsible for any preparatory work done before product arrival.