Product Sheet

meridian duo



Product No.

Model Alcove, Right	TMU BMDCRAORT-XX	Soaker BMDCRAORN-XX
Model Alcove, Left	TMU BMDCRAOLT-XX	Soaker BMDCRAOLN-XX

ThermoMasseur (TMU)

Air Jet System	\$4,265	
Jets	36	
1 heated backrest	Included	
Mia® Control	Included	
BU-Touch Control Application BUTOUCH	\$495	
Geysair®	Included	
AromaCloud®** BAROMAC	\$590	
Illuzio Chromatherapy BCHRO6	\$995	

Soaker	\$2,260	
AromaCloud®** BAROMAC	\$590	
Illuzio Chromatherapy BCHRO6	\$995	
WarmTouchShell® BWTS	\$1,125	
DOT Control	Included with therapy	

Options UPCHARGE APPLICABLE

Control (TMU only) p.13		
MiaPlus®# BMIAP1-XX	\$285	
Bath Pillow BPILLOW p.252	llow BPILLOW p.252 \$240	
Comfort Cushion BCUSHIONA p.253	\$540	
Grey 05 🗩 Black 02		
Drain & Overflow p.14	Integrated ZenFlow [†] <i>BOVERINZF-XX</i>	16" x 35" BOVER16-XX
Chrome 07	\$205	\$260
White 01 Biscuit 02	\$165	\$290
Brushed Nickel 09	\$205	\$290
Polished Nickel 10	\$205	\$290
Oil-rubbed Bronze 11	N/A	\$400
Matte Black 19 Satin Brass 18	\$260	N/A
If Required by Construction Code		

16" x 35" Cable driven brass drain & overflow kit BOVERBR \$240

Features

Installation Type	Alcove (3 walls)
No. of bathers 🕴 Imp. gallons 29 US gallons 35	
Integrated tile flange and removable panel (specify right or left)	Included
Standard Bath Color p.17	
White 01 Biscuit 02	Included

- [†] ZenFlow: Integrated overflow without a trim.
 ^{**} The AromaCloud® is built into the deck (factory installed).
 [#] The MiaPlus® Control is included when purchasing Chromatherapy.



Product Sheet

meridian duo

60" x 31" x 21"







Integrated tile flange

Technical Specifications



Letter	Description	Measure
A	Outside edge to center drain	10 3⁄8"
В	Outside edge to overflow	5 %"
С	Total length	60"
D	Total width	31"
E	Bathing well length	42 3⁄4"
F	Bathing well width	19 5/16"
G	Deck width	3 1⁄4"
н	Deck width at drain end	4"
I	Height from bottom of bath to top deck	21"
J	Tile flange height	1"
к	Height from bottom of drain to center of overflow	14 5%"
L	Maximum water level (Drain & overflow 16" x 35")	13"
м	Slope of backrest	23°

Will automatically be installed on the opposite side of the flage.
 Control position when factory-installed (Mia® or DOT) Turbine position (TMU)
 Indicates heated backrest (TMU) (i) Indicates WarmTouchShell® position (Soaker)

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.	Approx. shipping weight	136
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz,	Turbine power	550
	dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.	Air heater	600
Others	The Geysair® is located on the same side as the heated backrest. It must not be relocated. It must be connected to the hot water supply and be accessible (provide access).		
	Integrated tile flange is included (specify right or left). Integrated skirt with	Warranty	
	removable panel.	Controls-LED-Geysair*	5 ye

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog). 6 lb 0 W 0 W

Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

* Some restrictions apply | www.bainultra.com/warranty

Dimensions are subject to change; measured at external edges. Bathing well measured at air jet level. Tolerance: ±0.25" (±0.64 cm). Ensure bathtub is received prior to any construction. BainUltra® is not responsible for any preparatory work done before product arrival.