#### **Product Sheet**

# opus 6434

## Freestanding $64" \times 34" \times 25"$



### Product No.

Model Freestanding TMU BOS2RF00S Soaker BOS2RF00F

### ThermoMasseur (TMU) 👐

Air Jet System	Ş11,750
Jets	42
1 heated backrest	Included
MiaPlus® Control (not installed)	Included
BU-Touch Control Application BUTOUCH	Included

Soaker 👐

## \$7,995

**Options** UPCHARGE APPLICABLE

Bath Color p.17	
Black (glossy finish only) 06	\$500
Bath Pillow BPILLOW p.252	\$240
Drain & Overflow p.14	Integrated with trim BOVERIN-XX
White 01 Chrome 07	Incl.
Brushed Nickel 09	Incl.
Polished Nickel 10	Incl.
Matte Black 19 Satin Brass 18	\$125
<ul> <li>Black (glossy finish only) 06</li> </ul>	\$125
Island Tub Drain™*** p.15	
Island Tub Drain™ BISLDD	\$260
Cast Iron Island Tub Drain™ BISLDDCI	\$310
If Required by Construction Code or installed with ITD*	
Brass drain kit BDRCBF-XX Matte White 32 Brushed Nickel 09 Matte Black 19 Satin Brass 18	\$60

#### Features

Installation Type	Freestanding
No. of bathers 👬 Imp. gallons TMU 62 SOAKER 68 US gallons TMU 74 SOAKER 81 Armrests 2	
Integrated Drain & Overflow — with Trim BOVERINI-3	32
Matte White 32	Installed & Included
Standard Bath Color p.17	
🗇 White 01	Included
Finish	
Satin Finish Glossy Finish	Included

Made with FineStone® FineStone® is a high quality solid surface material composed of refined minerals and pure acrylic. Designed with care, this material is non porous, hygienic, and thermal insulant. Its satin finish is easy to clean and will maintain its properties through time.

#### Don't forget to indicate the finish for the Integrated drain & overflow and, if needed, for the Brass drain kit.

For FineStone® installed WITH ITD, you must order the Brass Drain Kit *BDRCBF* (upcharge). Specify finish.

\*\*\* An Island Tub Drain<sup>™</sup> and the Brass drain kit are required when there is no access under the bath.



https://bainultra.com/sites/default/ files/product\_files/product-sheetopus-6434.pdf For the installer Scan to view installation video (3:20 min) →



## opus 6434

Freestanding 64" x 34" x 25"







### **Technical Specifications**



Letter	Description	Measure TMU	Soaker
A	Total length	64"	64"
В	Total width	34"	34"
С	Bathing well length	48 15/16"	47 15/16"
D	Bathing well width	22 1⁄16"	23 1/8"
E	Deck width	1 5⁄8"	3/4"
F	Deck width	3/4"	3/4"
G	Total maximal height	24 ¾"	24 3⁄4"
н	Total minimal height	24"	24"
I	Base length	45 5/16"	43 1⁄16''
J	Slope of backrest	19°	23°
К	Maximum water level	18"	18 1⁄4''
L	Base width	23"	20 1/16"
Indica	ites heated backrest (TMU)		

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.	
Turbine	Access to the pump must be at least 18" x 22". Standard connection is a 15A, 120 V, 60 Hz, dedicated lines with a GFCI. Air vent necessary: 2" x 4" minimum.	
Others	The turbine must be remotely installed. Faucet must be freestanding or wall-mounted. Controls cannot be installed on the deck of the bath.	

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

TMU	Soaker
# 90000089	# 90000088
380 lb	285 lb
	550 W
	600 W
	# 90000089

#### Warranty

Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

\* Some restrictions apply | www.bainultra.com/warranty

Dimensions are subject to change; measured at external edges. Bathing well measured at air jet level. Tolerance:  $\pm 0.25$ " ( $\pm 0.64$  cm). Ensure bathtub is received prior to any construction. BainUltra® is not responsible for any preparatory work done before product arrival.